



1. Dry Weight - 650 kg
2. Certified to AS/NZS:4766:2020
- 3*. Due to the moulding process, measurements will vary between tanks



Promax

LIQUID MANAGEMENT SOLUTIONS

THIS DOCUMENT (AND THE INFORMATION SHOWN THEREON) IS CONFIDENTIAL AND PROPRIETARY AND SHALL NOT BE DISCLOSED TO OTHERS IN HARD COPY OR ELECTRONIC FORM, REPRODUCED BY ANY MEANS, OR USED FOR ANY PURPOSE WITHOUT WRITTEN CONSENT OF PROMAX PLASTICS LIMITED.

UNLESS OTHERWISE SPECIFIED THE INFORMATION WITHIN THIS TITLE BLOCK SHALL APPLY

| | | |
|---|--|-----------|
| DIMENSIONS ARE IN: MM UNSPECIFIED DIMS IN 3D * DIMENSIONS FOR REFERENCE | | CAGE CODE |
| MATERIAL | | |
| FINISH | | |

| | | |
|--|-----------|------------------------|
| DESIGNED BY | A.P. | 22 AUG 2021 |
| DESIGNED BY | | |
| CHECK BY | | |
| APPROVED BY | J.A. | 22 AUG 2021 |
| TITLE | | |
| Promax Super Duty Underground Tank - 8000L | | |
| SIZE | DWG NO | REV |
| A3 | US1008000 | - |
| SCALE | 1:18 | MASS UNSP SHEET 1 OF 1 |