

OPERATION AND MAINTENANCE GUIDES

O&M For:	UEST05000DB
Date:	August 2023
Code:	UEST05000DB
Description:	ENDURO Septic Tank 5,000 Ltr 1.0 Dia
Product Warranty:	5 years

SPECIFICATIONS

	Capacity (L)	Length (mm)	Width (mm)	Weight (kg)	Manhole Dia (mm)
	5000	5071	1250	250	600
Standard	Includes 1x 100mm outlets Complies with: <ul style="list-style-type: none">• AS/NZS:1546 Standard for Septic Tanks				
Uses	• Primary Treatment of Septic Waste				
Statement	In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions. Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.				

MAINTENANCE

Description	Action	Frequency
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sludge Build Up	Remove sludge with vacuum truck. Re-attach tank lid securely.	Minimum 3 years or as necessary

Please note: Entry into this tank is at owners risk.

