

OPERATION AND MAINTENANCE GUIDES

O&M For:	SL1P05000
Date:	July 2022
Code:	SL1P05000
Description:	Promax Slimline Tank & Pump 5,000 Ltr
Product Warranty:	5 years

SPECIFICATIONS

	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Manhole Dia (mm)
	3000	910	2150	270	350
Standard	Includes 1x 25mm outlets Complies with: <ul style="list-style-type: none">•AS/NZS 4020: Products in contact with drinking water.•AS/NZS 2070: Plastics material for food contact use.				
Uses	<ul style="list-style-type: none">• Water Storage• Retention/Detention Stormwater Management				
Statement	In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions. Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.				

MAINTENANCE

Description	Action	Frequency
Tank Stability	Tank must remain level, foundation must not become eroded	Monthly
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sediment Build Up	Remains lower than base outlet - if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

Please note: Entry into this tank is at owners risk.



