OPERATION AND MAINTENANCE GUIDES



O&M For:	EI1010000	
Date:	November 2023	
Code:	El1010000	
Description:	ENDURO Industrial Tank 10,000 Ltr - North Island	
Product Warranty:	1 year	

SPECIFICATION	ONS				
	Capacity (L)	Diameter (mm)	Height (mm)	Outlets	Manhole Dia (mm)
	10,000	2165	2900	1 ×50	450
Standard	Complies with: • AS/NZS 4020: Products in contact with drinking water • AS/NZS 2070 (INT): Plastics material for food contact use • Certified to AS/NZS 4766:2006: Water & Chemical Tank Standard				
Uses	Potable Water StorageRetention/Detention Stormwater ManagementIndustrial Applications				
Statement	Ratings, Promax	is committed to supply	ring quality Liquid S	Storage and Handli	ling Initiatives and 5 Star ng Solutions. 1anagement practices set

MAINTENANCE

Description	Action	Frequency
Tank Stability	Tank must remain level, foundation must not become eroded	Monthly
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sediment Build Up	Remains lower than base outlet - if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary

out in the Promax Installation Guides, they will perform as stated throughout their intended life.

Please note: Entry into this tank is at owners risk.

OPERATION AND MAINTENANCE GUIDES



Responsibility: The owner/s are responsible for maintenance of the tank.

Post Storm Inspection: Following a storm event it is recommended that a full tank inspection is carried out, please refer

the maintenance section for guidelines on this.

Debris removal programme:

If debris is identified in either a regular maintenance check or post storm inspection it is recommended that this is removed by a professional stormwater maintenance provider.

MAINTENANCE RECORDS

Date	Comments	Completed