

OPERATION AND MAINTENANCE GUIDES

O&M For:	UELP01500DB
Date:	October 2025
Code:	UELPO1500DB
Description:	ENDURO LOW PROFILE UNDERGROUND TANK 1,500 LTR
Product Warranty:	10 years

SPECIFICATIONS					
	Width (mm)	Height (mm)	Length (mm)	Weight (kg)	Manhole Dia (mm)
	1250	1000	4070	100	250
Standard	Complies with: • AS/NZS 4020: Products in contact with drinking water • AS/NZS 2070 (INT): Plastics material for food contact use				
Uses	• Portable Water Storage • Retention/Detention Stormwater Management • Waste Storage				
Statement	In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions. Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.				

MAINTENANCE			
Description	Action	Frequency	
Tank Lid	Remains securely fitted	Bi-Monthly	
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly	
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly	
Sediment Build Up	Remains lower than base outlet – if outlet flow becomes restricted remove sediment with vacuum truck. Re-attach tank lid securely.	Half yearly or as necessary	

Please note: Entry into this tank is at owners risk.

Promax
LIQUID MANAGEMENT SOLUTIONS

Debris removal programme: If debris is identified in either a regular maintenance check or post storm inspection it is recommended that this is removed by a professional stormwater maintenance provider.

[illegible]

Authorised By:
Promax Engineered Plastics Limited
PO Box 749, Kerikeri 0245, New Zealand
T: 0800 77 66 29
E: sales@promaxplastics.co.nz

promaxplastics.co.nz