

# Product Specification and Maintenance Guide

## PSMG-PMXAC01300PSBLK

<b>Date</b>	September 2021
<b>Code</b>	PMXAC01300PSBLK
<b>Description</b>	Promax Pump Chamber 1300L

### Specifications

Capacity (L)	Diameter (mm)	Height (mm)	Manhole Dia (mm)
1300	1000	2070	600

<b>Uses</b>	<ul style="list-style-type: none"><li>In-ground protective chamber for holding and accessing pumps for septic, stormwater and wastewater.</li></ul>
-------------	---

<b>Statement</b>	<p>In line with today's focus on Ecologically Sustained Development, Green Building Initiatives and 5 Star Ratings, Promax is committed to supplying quality Liquid Storage and Handling Solutions</p> <p>Promax Plastics confirms that if these tanks are installed according to Good Management practices set out in the Promax Installation Guides, they will perform as stated throughout their intended life.</p>
------------------	--

### Maintenance

Description	Action	Frequency
Tank Lid	Remains securely fitted	Bi-Monthly
Inlet/Outlet Fitting	Remains securely fitted with no leakage	Bi-Monthly
Pump	Check Pump, if fitted, for inlet screen blockages	Bi-Monthly
Sludge Build Up	Remove sludge with vacuum truck. Re-attach tank lid securely.	Minimum 3 years or as necessary

**Please note: Entry into this tank is at owners risk.**

### Authorised By:

Promax Engineered Plastics Limited  
PO Box 749, Kerikeri 0245, New Zealand



